

12mm标准行星齿轮箱

典型应用：眉笔、照相机、保健用品、自动浇灌设备等
Typical Application: Eyebrow pencil, Camera, Health care product, Auto watering device, and etc.

Standard Metal Geared Motor

输出功率：约**0.01W~7.5W**
Output Power: **0.01W~7.5W**

金属输出轴
Metal output shaft

型号 Model	典型应用参数 Typical Application Parameters							Max Rated Torque of Gear Box 齿轮箱额定 容许力矩	Max Instant Torque of Gear Box 齿轮箱瞬间 容许力矩	Gear Ratio 减速比	Gear Box Length 减速箱长 L1	
	Rated 额定值	At No Load 空载数据		At Rated Load 负载数据			Overall Length 总长 L					
	Voltage 电压	Speed 转速	Current 电流	Speed 转速	Current 电流	Torque 转矩						
	VDC	rpm	mA(MAX)	rpm	mA(MAX)	gf.cm mN.m					mm	gf.cm
12mm-4速比	12.0	5936	107	5112	755	88	8.6	43.2	2000	6000	4	13.2
12mm-6速比	12.0	3957	107	3408	755	132	13.0		2000	6000	6	
12mm-16速比	12.0	1456	112	1278	755	300	29.4	47.0	2000	6000	16	17.0
12mm-24速比	12.0	971	112	852	755	450	44.1		2000	6000	24	
12mm-36速比	12.0	647	112	568	755	675	66.2		2000	6000	36	
12mm-64速比	12.0	361	112	320	760	900	88.2	50.8	2000	6000	64	20.8
12mm-96速比	12.0	240	112	213	760	1529	150.0		2000	6000	96	
12mm-144速比	12.0	160	112	142	760	2294	225.0		2000	6000	144	
12mm-216速比	12.0	107	112	95	760	3441	337.5		2000	6000	216	
12mm-256速比	12.0	90	117	80	760	3467	340.0	54.6	2000	6000	256	24.6
12mm-384速比	12.0	60	117	53	760	5200	510.0		2000	6000	384	
12mm-576速比	12.0	40	117	36	760	7800	764.9		2000	6000	576	
12mm-864速比	12.0	27	117	24	760	11700	1147.4		2000	6000	864	
12mm-1296速比	12.0	18	117	16	760	17550	1721.1		2000	6000	1296	

* Above specifications are subject to change without notice, just for reference and customizable according to requirements
上规格数据仅供参考，如有修改恕不另行通知，可按需求定制

* 以

