

20mm金属行星减速箱

典型应用：自动机械传动、医疗器械、广告旋转传动、自动取款机等
Typical Application: Automechanism transmission, Medical instrument, Ad rotaion transmission, ATM , and etc.

Standard Metal Geared Motor

输出功率：约0.5W~18W
Output Power: 0.5W~18W

金属输出轴
Metal output shaft

型号 Model	典型应用参数 Typical Application Parameters							Max Rated Torque of Gear Box 齿轮箱额定 容许力矩	Max Instant Torque of Gear Box 齿轮箱瞬间 容许力矩	Gear Ratio 减速比	Gear Box Length 减速箱长 L1	
	Rated 额定值	At No Load 空载数据		At Rated Load 负载数据			Overall Length 总长 L					
	Voltage 电压	Speed 转速	Current 电流	Speed 转速	Current 电流	Torque 转矩						
	VDC	rpm	mA(MAX)	rpm	mA(MAX)	gf.cm	mN.m	mm	gf.cm	gf.cm	mm	
20mm-4速比	24.0	4273	118	4041	655	314	30.8	57.6	10000	36000	4	17.6
20mm-6速比	24.0	2848	118	2694	655	470	46.1		10000	36000	6	
20mm-16速比	24.0	1068	128	1010	655	1004	98.4	62.9	10000	36000	16	22.9
20mm-16速比	24.0	712	128	674	655	1505	147.6		10000	36000	24	
20mm-36速比	24.0	475	128	449	655	2258	221.4		10000	36000	36	
20mm-64速比	24.0	267	138	253	655	2646	259.5	68.2	10000	36000	64	28.2
20mm-96速比	24.0	178	138	168	655	3969	389.2		10000	36000	96	
20mm-144速比	24.0	119	138	112	655	5954	583.9		10000	36000	144	
20mm-216速比	24.0	79	138	75	655	8930	875.8		10000	36000	216	
20mm-256速比	24.0	64	138	63	660	7938	778.5	73.5	10000	36000	256	33.5
20mm-384速比	24.0	43	138	42	660	10000	981		10000	36000	384	
20mm-576速比	24.0	28	138	28	660	10000	981		10000	36000	576	
20mm-864速比	24.0	19	138	19	660	10000	981		10000	36000	864	
20mm-1296速比	24.0	13	138	12	660	10000	981		10000	36000	1296	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

*以上规格数据仅供参考，如有修改恕不另行通知，可按需求定制

