

22mm金属齿轮箱

典型应用：光学设备、医疗器械、广告旋转传动、银行提款机等
Typical Application: Optical device, Medical apparatus and instruments, Advertising rotating drive, Bank machines, and etc.

Standard Metal Geared Motor

输出功率：约0.5W~25W
Output Power: 0.5W~25W

金属输出轴
Metal output shaft

型号 Model	典型应用参数 Typical Application Parameters							Max Rated Torque of Gear Box 齿轮箱额定 容许力矩	Max Instant Torque of Gear Box 齿轮箱瞬间 容许力矩	Gear Ratio 减速比	Gear Box Length 减速箱长 L1	
	Rated 额定值	At No Load 空载数据		At Rated Load 负载数据			Overall Length 总长 L					
	Voltage 电压	Speed 转速	Current 电流	Speed 转速	Current 电流	Torque 转矩						
	VDC	rpm	mA(MAX)	rpm	mA(MAX)	gf.cm	mN.m	mm	gf.cm	gf.cm	mm	
22mm-4速比	24.0	3100	104	3040	625	564	55.4	67.1	15000	36000	4	19.1
22mm-6速比	24.0	2067	104	2027	625	847	83.0		15000	36000	6	
22mm-16速比	24.0	775	114	760	625	1806	177.1	74.4	15000	36000	16	26.4
22mm-24速比	24.0	517	114	507	625	2710	265.7		15000	36000	24	
22mm-36速比	24.0	344	114	338	625	4064	398.6		15000	36000	36	
22mm-64速比	24.0	194	124	190	625	4763	467.1	81.7	15000	36000	64	33.7
22mm-96速比	24.0	129	124	127	625	7144	700.6		15000	36000	96	
22mm-144速比	24.0	86	124	84	625	10716	1050.9		15000	36000	144	
22mm-216速比	24.0	57	124	56	625	15000	1471.1		15000	36000	216	
22mm-256速比	24.0	46	124	47	630	14288	1401.3	89	15000	36000	256	41
22mm-384速比	24.0	31	124	32	630	15000	1471.1		15000	36000	384	
22mm-576速比	24.0	21	124	21	630	15000	1471.1		15000	36000	576	
22mm-864速比	24.0	14	124	14	630	15000	1471.1		15000	36000	864	
22mm-1296速比	24.0	9	124	9	630	15000	1471.1		15000	36000	1296	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

*以上规格数据仅供参考，如有修改恕不另行通知，可按需求定制

