

28mm金属行星齿轮箱

典型应用：光学设备、医疗器械、广告旋转传动、银行提款机等
Typical Application: Optical device, Medical apparatus and instruments, Advertising rotating drive, Bank machines, and etc.

Standard Plastic Geared Motor

输出功率：约0.5W~30W
Output Power: 0.5W~30W

金属输出轴
Metal output shaft

型号 Model	典型应用参数 Typical Application Parameters							Max Rated Torque of Gear Box 齿轮箱额定 容许力矩	Max Instant Torque of Gear Box 齿轮箱瞬间 容许力矩	Gear Ratio 减速比	Gear Box Length 减速箱长 L1	
	Rated 额定值	At No Load 空载数据		At Rated Load 负载数据			Overall Length 总长 L				mm	
	Voltage 电压	Speed 转速	Current 电流	Speed 转速	Current 电流	Torque 转矩						
	VDC	rpm	mA(MAX)	rpm	mA(MAX)	gf.cm						mN.m
28mm-4速比	24.0	2084	160	1771	400	1098	107.6	79.3	40000	120000	4	21.3
28mm-6速比	24.0	1389	160	1181	400	1646	161.5		40000	120000	6	
28mm-16速比	24.0	472	150	413	400	3512	344.5	87.8	40000	120000	16	29.8
28mm-24速比	24.0	312	150	276	400	5268	516.7		40000	120000	24	
28mm-36速比	24.0	211	150	181	400	7903	775.0		40000	120000	36	
28mm-64速比	24.0	119	150	111	350	9261	908.2	96.3	40000	120000	64	38.3
28mm-96速比	24.0	79	150	74	350	13892	1362.3		40000	120000	96	
28mm-144速比	24.0	54	150	49	350	20837	2043.5		40000	120000	144	
28mm-216速比	24.0	35	150	33	350	31256	3065.3		40000	120000	216	
28mm-256速比	24.0	30	150	28	350	27783	2724.7	104.8	40000	120000	256	46.8
28mm-384速比	24.0	19	150	18	350	40000	3922.8		40000	120000	384	
28mm-576速比	24.0	13	150	12	350	40000	3922.8		40000	120000	576	
28mm-864速比	24.0	9	150	8	350	40000	3922.8		40000	120000	864	
28mm-1296速比	24.0	6	150	5	350	40000	3922.8		40000	120000	1296	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

*以上规格数据仅供参考，如有修改恕不另行通知，可按需求定制

