

38mm金属行星齿轮箱

典型应用：割草机、流量泵、电动门窗、天线基站等

Typical Application: The lawn mower, Flow pump, Electric windows and doors, Base station antenna and etc.

Standard Metal Geared Motor

输出功率：约2.8W~75W

Output Power: 2.8W~75W

金属输出轴

Metal output shaft

型号 Model	典型应用参数 Typical Application Parameters							Max Rated Torque of Gear Box 齿轮箱额定容 许力矩	Max Instant Torque of Gear Box 齿轮箱瞬间 容许力矩	Gear Ratio 减速比	Gear Box Length 减速箱长 L1	
	Rated 额定值	At No Load 空载数据		At Rated Load 负载数据			Overall Length 总长 L					
	Voltage 电压	Speed 转速	Current 电流	Speed 转速	Current 电流	Torque 转矩						
	VDC	rpm	mA(MAX)	rpm	mA(MAX)	gf.cm	mN.m			mm	gf.cm	gf.cm
38mm-4速比	24.0	1490	175	1348	3615	4092	401.3	100.7	80000	240000	4	30.7
38mm-6.25速比	24.0	953	175	863	3615	6395	627.1		80000	240000	6.25	
38mm-16速比	24.0	372	185	337	3615	14242	1396.7	113.7	80000	240000	16	43.7
38mm-25速比	24.0	238	185	216	3615	22253	2182.3		80000	240000	25	
38mm-39速比	24.0	153	185	138	3615	34714	3404.4		80000	240000	39	
38mm-64速比	24.0	93	195	84	3615	49562	4860.5	126.7	80000	240000	64	56.7
38mm-100速比	24.0	60	195	54	3615	77440	7594.5		80000	240000	100	
38mm-156速比	24.0	38	195	35	3615	80000	7845.6		80000	240000	156	
38mm-244速比	24.0	24	195	22	3615	80000	7845.6		80000	240000	244	
38mm-256速比	24.0	22	195	21	3620	80000	7845.6	139.7	80000	240000	256	69.7
38mm-400速比	24.0	14	195	13	3620	80000	7845.6		80000	240000	400	
38mm-625速比	24.0	9	195	9	3620	80000	7845.6		80000	240000	625	
38mm-977速比	24.0	6	195	6	3620	80000	7845.6		80000	240000	977	
38mm-1526速比	24.0	4	195	4	3620	80000	7845.6		80000	240000	1526	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

*以上规格数据仅供参考，如有修改恕不另行通知，可按需求定制

